

- For cooling, heating or dual temperature service.

- Friendly Feel Duct Wrap—meets the most stringent IAQ tests—GREENGUARD Children & Schools and California's Section 01350 standard.

- The white facing offers exceptional durability and performance for exposed applications.



Facts at a glance

- Fire-resistant facing
- Conforms to flat or irregular surfaces
- Excellent acoustical properties
- ECOSE Technology is a revolutionary binder based on rapidly renewable bio-based materials rather than non-renewable petroleum-based chemicals such as phenol, formaldehyde, acrylics, artificial colors or UREA.



Knauf Exeed Insulation LLC
Mussafah ICAD1
P.O. Box 34332, Abu Dhabi, UAE

Tel. +971 2 551 2453

Fax +971 2 551 2451

sales@kei.ae

www.knaufexeedinsulation.ae



LEED Eligible Product
Use of this product may help building projects meet green building standards as set by the Leadership in Energy and Environmental Design (LEED) Green Building Rating System.
Credit 4.1 - 4.2 Recycled Content
Credit 5.1 - 5.2 Regional Materials



Knauf Insulation Friendly Feel® Duct Wrap with ECOSE® Technology is certified for indoor air quality as a low emitting product by the GREENGUARD Environmental Institute to both the GREENGUARD Indoor Air Quality Certification ProgramSM and the more stringent GREENGUARD Children & SchoolsSM standard and is verified to be formaldehyde free.

www.greenguard.org

Data Sheet

November 2013

Friendly Feel® Duct Wrap with ECOSE® Technology



Friendly Feel® Duct Wrap with ECOSE® Technology

Description

Knauf Insulation Friendly Feel® Duct Wrap with ECOSE® Technology is a thermal and acoustical insulation blanket made from highly resilient Glass Mineral Wool bonded by ECOSE Technology. It is available unfaced, with a foil-scrim-kraft (FSK) jacket and with a white All Service Jacket (ASJ). Vapor retarders provide a 2" (51 mm) staple flange on one edge, and the factory-applied facing assures uniform quality.

ECOSE Technology

ECOSE Technology is a revolutionary binder chemistry that makes Knauf Insulation products even more sustainable than ever. It features rapidly renewable bio-based materials rather than non-renewable petroleum-based chemicals traditionally used in Glass Mineral Wool insulation products. ECOSE Technology reduces binder embodied energy and does not contain phenol, formaldehyde, acrylics, artificial colors or UREA.

Application

Knauf Insulation Friendly Feel Duct Wrap is used as external insulation on commercial or residential heating or air conditioning ducts. It is suitable for the exterior of rectangular or round sheet metal ducts and spaces or surfaces where temperature and condensation must be controlled.

Features and Benefits

- Low "k" factor significantly reduces heat gain or loss when applied with proper compression
- Flexible
- Lightweight
- Excellent acoustical properties
- Tough and resilient
- Energy conservation, which lowers operating costs
- System efficiency increases; energy usage/costs decrease
- Conforms easily to flat or irregular surfaces
- Rolls allow for faster installation, lower labor costs
- Reduces sound transmission through the duct wall
- Assured condensation control when used with FSK or ASJ facings, proper installation and sealed joints, seams and penetrations
- Resists damage in shipment and during and after installation
- Knauf Insulation achieved GREENGUARD Gold Certification and is verified to be formaldehyde free. Products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. Knauf Insulation has achieved a UL Environment claim validation for

over 50% post-consumer recycled glass content in our insulation products.

Sustainability

- Carbon-negative, meaning Knauf Insulation products used for thermal insulating purposes recover the energy that it took to make them in just hours or a few days, depending on the application. Once installed, the product continues to save energy and reduce carbon generation as long as it is in place.
- Glass Mineral Wool insulation with ECOSE Technology contains three primary ingredients:
 - Sand, one of the world's most abundant and renewable resources
 - A minimum 50% recycled post-consumer glass content and UL Environment verification every 6 months
 - ECOSE Technology which reduces binder embodied energy by up to 70%

Specification Compliance

- ASTM C 1139 - unfaced; Type I, Type II, Grade 1 - 0.75 lb/ft³
Grade 2 - 1.0 lb/ft³
Grade 3 - 1.5 lb/ft³
- ASTM C 553; Type I, II, III
- ASTM C 1136; Type II
- ASTM C 1290
- GREENGUARD GOLDSM and verified to be formaldehyde free
- NFPA 90A and 90B

Technical Data

Surface Burning Characteristics

- UL/ULC Classified FHC 25/50 (FSK, Unfaced)
- Unfaced and FSK wrap have a Flame Spread 25 and Smoke Developed 50 when tested in accordance with ASTM E 84, CAN/ULC S102-M88, NFPA 255 and UL 723. ASJ wrap has a Flame Spread 25 and Smoke Developed 50 when tested in accordance with ASTM E 84.

Temperature Range (ASTM C 411)

- Faced, can be used on ducts operating up to 250°F (121°C)
- Unfaced, up to 350°F (177°C)

Water Vapor Permeance (ASTM E 96, Procedure A)

- FSK and white ASJ facings have maximum water vapor permeance of .02 perms.

Water Vapor Sorption (ASTM C 1104)

- Less than 5% by weight when tested for 96 hours at 120°F (49°C) and 95% relative humidity

Corrosiveness (ASTM C 665)

- Does not accelerate corrosion on steel, copper or aluminum

Corrosion (ASTM C 1617)

- The corrosion rate in mils/yr will not exceed that of the 1 ppm chloride solution.

Mold Growth (ASTM C 1338)

- No growth

Puncture Resistance (TAPPI Test T803) (Beach Units)

- FSK and ASJ: 25

Application & Specification Guidelines

Storage

- Protect stored insulation from water damage, construction damage and other abuse.
- If stored outside, proper protection from weather conditions should be provided.

Preparation

- Install Knauf Insulation Friendly Feel Duct Wrap over clean, dry sheet metal ducts.
- All sheet metal joints and seams must be sealed to prevent air leakage from the duct.

Application

- Install Knauf Insulation Friendly Feel Duct Wrap with facing to the outside to obtain specified R-value using a maximum of 25% compression.
- Butt all insulation joints firmly together. Longitudinal seam of the vapor retarder must be overlapped a minimum of 2" (51 mm). A 2" (51 mm) tab is provided for the circumferential seam and must be overlapped.
- Where vapor retarder performance is necessary, all penetrations, joints, seams and damage to the facing should be sealed with an FSK, ASJ or foil tape or glass fabric and mastic prior to system startup.
- Pressure sensitive tapes should be a minimum 3" (76 mm) wide and be applied with moving pressure using an appropriate sealing tool. Staples should be outward clinch and placed approximately 6" (152 mm) on center.
- Closure systems should have a 25/50 F.H.C. per UL 723.
- For rectangular ducts over 24" (610 mm) wide, secure the insulation to the bottom side of the duct with mechanical fasteners spaced on 18" (457 mm) centers to reduce sag. Care should be taken to avoid overcompressing the insulation with the retaining washer.
- It is neither necessary nor desirable to adhere duct wrap to duct surfaces with adhesive.

- Unfaced Duct Wrap should be overlapped with a minimum of 2" (51 mm) and fastened with 4" (102 mm) to 6" (152 mm) nails or skewers placed 4" (102 mm) apart, or secured with a wire or banding system. Care must be taken to avoid damaging the duct wrap. Refer to diagram for staple stitching and butt-joint method.

Installation Procedures

- Use the table (right inside fold) to determine stretch-outs required for the nominal thickness of insulation to limit average compression of the insulation 25% or less.


Glass Mineral Wool and Mold

Glass Mineral Wool insulation will not sustain mold growth. However, mold can grow on almost any material when it becomes wet and contaminated. Carefully inspect any insulation that has been exposed to water. If it shows any sign of mold, it must be discarded. If the material is wet but shows no evidence of mold, it should be dried rapidly and thoroughly. If it shows signs of facing degradation from wetting, it should be replaced. Air handling insulation used in the air stream must be discarded if exposed to water.

Notes

The chemical and physical properties of Knauf Insulation Friendly Feel Duct Wrap represent typical average values determined in accordance with accepted test methods. The data is subject to normal manufacturing and testing variations. The data is supplied as a technical service and is subject to change without notice. References to numerical flame spread ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions.

Check with your Knauf Insulation sales representative to assure information is current.



Stretch-Outs				
Labeled Thickness	Installed Compressed Thickness	Round	Square	Rectangular
1½" (38 mm)	1½" (29 mm)	P+9 ½" (241 mm)	P+8" (203 mm)	P+7" (178 mm)
2" (51 mm)	1½" (38 mm)	P+12" (305 mm)	P+10" (254 mm)	P+8" (203 mm)
2½" (64 mm)	1½" (42 mm)	P+13" (330 mm)	P+11" (279 mm)	P+8½" (216 mm)
2½" (64 mm)	1½" (48 mm)	P+14½" (368 mm)	P+12½" (318 mm)	P+9½" (241 mm)
3" (76 mm)	2¼" (57 mm)	P+17" (432 mm)	P+14½" (368 mm)	P+11½" (292 mm)

P = Perimeter of duct to be installed.

Forms Available/R-Values@75°F Mean Temperature						
Density	Thickness	Width	Length	Facing	Out-Of Package R-Value	Installed R-Value
.75 PCF (12 kg/m ³)	1½" (38 mm)	1.2 m	100' (30.48 m)	FSK, ASJ unfaced	5.1	4.2
	2" (51 mm)		75' (22.86 m)		6.8	5.6
	2½" (64 mm)		75' (22.86 m)		7.4	6.0
2½" (64 mm)	50' (15.24 m)	8.5	7.0			
3" (76 mm)	50' (15.24 m)	10.2	8.4			
1.0 PCF (16 kg/m ³)	1½" (38 mm)	1.2 m	100' (30.48 m)		5.6	4.5
1.5 PCF (24 kg/m ³)	2" (51 mm)	1.2 m	75' (22.86 m)	7.4	6.0	
	1½" (38 mm)		75' (22.86 m)	6.1	4.8	
	2" (51 mm)		50' (15.24 m)	8.2	6.4	

Insertion Loss (Reduction of Sound Transmitted Through Duct Wall) (Sound and Vibration Design and Analysis, National Environmental Balancing Bureau, 1994)											
Duct Dimensions	Sheet Metal	Duct Wrap			Insertion Loss, dB/LF of Duct						
		Nominal Thickness	Nominal Density		63Hz	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz
12" x 12" (305 mm x 305 mm)	24 GA	1½" (38 mm)	.75 PCF (12 kg/m ³)		.6	.6	.6	.7	7.4	14.2	20.9
24" x 12" (610 mm x 305 mm)	24 GA	1½" (38 mm)	.75 PCF (12 kg/m ³)		.6	.6	.6	.7	7.4	14.2	20.9
48" x 12" (1219 mm x 305 mm)	22 GA	1½" (38 mm)	.75 PCF (12 kg/m ³)		.5	.5	.5	.6	7.4	14.1	20.9
24" x 24" (610 mm x 610 mm)	22 GA	1½" (38 mm)	.75 PCF (12 kg/m ³)		.5	.5	.5	.6	7.4	14.1	20.9
24" x 12" (610 mm x 305 mm)	26 GA	1½" (38 mm)	.75 PCF (12 kg/m ³)		.8	.8	.8	.8	7.5	14.2	21.0
24" x 8" (610 mm x 203 mm)	26 GA	2" (51 mm)	.75 PCF (12 kg/m ³)		1.0	1.0	1.0	3.6	10.4	17.1	23.9

Condensation Control (Recommended minimum install R-Values for condensation control on flat surfaces. Surface emittance : 0.2 (aged aluminum foil or galvanized sheet metal).)															
RH	Operating Temperature														
	45°F (7°C)					55°F (13°C)					60°F (18°C)				
	Ambient Temperature (°F)					Ambient Temperature (°F)					Ambient Temperature (°F)				
	70	80	90	100	110	70	80	90	100	110	70	80	90	100	110
60	2.2 ¹	3.3 ¹	4.3 ²	4.3 ²	5.4 ³	1.1 ¹	2.2 ¹	3.3 ¹	3.3 ¹	4.3 ²	1.1 ¹	1.1 ¹	2.2 ¹	3.3 ¹	4.3 ²
70	3.3 ¹	5.4 ³	6.5 ⁴	7.6 ³	—	1.1 ¹	3.3 ¹	4.3 ²	6.5 ⁴	6.5 ⁴	1.1 ¹	1.1 ¹	3.3 ¹	5.4 ³	6.5 ⁴
80	7.0 ⁴	—	—	—	—	3.3 ¹	6.5 ⁴	—	—	—	2.2 ¹	3.3 ¹	6.5 ⁴	—	—
90	—	—	—	—	—	—	—	—	—	—	6.5 ⁴	—	—	—	—

¹ All Duct Wrap products

² 0.75 PCF, 2" and greater; 1.0 PCF, 1½" and greater; 1.5 PCF, 1½" and greater

³ 0.75 PCF, 2" and greater; 1.0 PCF, 2"; 1.5 PCF, 2"

⁴ 0.75 PCF, 2½" and greater

